




Filter Collectors

Clear rainwater for domestic and garden use


- The unique construction of the vertically placed fine filter harvests more than 90 % of clear rainwater whilst automatically - separating out dirt and debris
- The WISY filter collectors are available in different types and sizes for installation in vertical metal or plastic rainwater downpipes/ downspouts
- Completely safe and reliable operation
- Easy installation
- Meets DIN EN 12056, 752 (Drainage safety) and DIN 1989 (Rainwater harvesting)
- Low maintenance, filter is virtually self-cleaning



 **made
in
Germany**

Housing is made of stainless steel or Copper. Nominal sizes (DN) 100, -87, -80, -76.


Filter insert (mesh size 0,28 mm or 0,44 mm) of stainless-steel.



- 1 Upper housing
- 2 Filter insert
- 3 Housing
- 4 Collecting space
- 5 Filtered water outlet to the storage tank

Filter collector (FS):

- The rainwater coming from the roof through the downpipe / downspout is drawn sideways through the vertically orientated stainless-steel filter insert by adhesion forces. Filtered water falls into the collecting space and is fed via the outlet connection (DN 50) to the storage tank.
- The full cross-section of the rainwater drainage system remains continuously open. With no obstruction or narrowing of the downpipe/ downspout. Even in the event of hailstorms




and torrential rainfall 50 % of the water is filtered and transferred to the storage tank. Excess rainwater is led directly to the drain or to infiltration.

Standpipe filter collector (STFS)

Advantages:

- Installation of the tank inlet below ground, i.e. no second pipe is visible.
- Larger collecting space and therefore greater efficiency in case of rainstorms


Housing is made of stainless-steel, for nominal size (DN) 100, -87, -80, -76. Filter insert (mesh size 0,28 mm or 0,44 mm) of stainless-steel. For underground connection to the storage (DN 50 outlet)



The stainless-steel standpipe clip (accessory)



- 1 Upper housing
- 2 Filter insert
- 3 Housing
- 4 Collecting space
- 5 Filtered water outlet to the storage tank




Garden rainwater filter (GRS):

WISY offers a large range of connecting parts especially for the garden rainwater filter.


WISY garden rainwater barrel "Stabilix"



Especially for rainwater barrels in the garden. For installation in rainwater downpipes / downspouts. Outlet to the storage tank DN 50. Of stainless steel. Available with or without filter insert (mesh size 0,44 mm). For nominal sizes (DN) 100, -87, -80, -76.



Blind insert



Replaces the filter insert to prevent any water flow to the storage tank f.i. during maintenance etc. Diverts all flow to the drain or infiltration.



WISY AG
D-63699 Kefenrod, Oberdorfstraße 26
Telefon +49 (0) 60 54-91 21-0

Fax +49 (0) 60 54-91 21-29
Internet: www.wisy.de
E-Mail: info@wisy.de